Heanjia Super-Metals Co., Ltd

Inconel 600 Mesh



Woven Inconel 600 Mesh

Perforated Inconel 600 Metal



Expanded Inconel 600 Metal

Heanjia Super-Metals supplies an exclusive range of Inconel 600 mesh products to deliver the exemplary performance; we recommend design and offer a completely customized solution for your application. Our target is to provide complete satisfaction with the service of products. We trust we can deliver the right components that you require. We always make efforts to keep your price competitive by offering the highest quality Inconel 600 mesh solutions.

Inconel 600 Mesh is made in the various styles:

- Inconel 600 Wire Mesh
- Inconel 600 Expanded Metal
- Inconel 600 Perforated Metal

Inconel 600 Mesh Applications

High temperature support screens	Mesh for high temperature	Filters	Fire guards	re guards	
Heat processing equipments	Screening and sieving	Aerospace engineering		Strainers and baskets	

Inconel 600 Mesh Specifications

Mesh	Wire diameter		SWG	Aperture		Open area	Weight
2 Mesh	0.080 ins	2.00 mm	14	0.420 ins	10.66 mm	71%	4.01 kg/m ²
5 Mesh	0.036 ins	0.90 mm	20	0.164 ins	4.16 mm	67%	2.03 kg/m ²
8 Mesh	0.022 ins	0.56 mm	24	0.103 ins	2.62 mm	68%	1.24 kg/m ²
12 Mesh	0.028 ins	0.71 mm	22	0.055 ins	1.41 mm	44%	3.10 kg/m ²
14 Mesh *	0.020 ins	0.50 mm	25	0.051 ins	1.31 mm	52%	1.79 kg/m²
16 Mesh *	0.022 ins	0.56 mm	24	0.041 ins	1.03 mm	42%	2.49 kg/m²
16 Mesh	0.018 ins	0.45 mm	26	0.045 ins	1.13 mm	51%	1.65 kg/m²
18 Mesh	0.012 ins	0.32 mm	30	0.043 ins	1.10 mm	60%	0.88 kg/m²
24 Mesh	0.012 ins	0.315 mm	30	0.029 ins	0.74 mm	49%	1.18 kg/m²
120 Mesh	0.0032 ins	0.080 mm	44	0.0051 ins	0.130 mm	37%	0.39 kg/m²
130 Mesh	0.0036 ins	0.090 mm	43	0.0041 ins	0.104 mm	28%	0.53 kg/m²
300 Mesh	0.0014 ins	0.036 mm	48.5	0.0019 ins	0.048 mm	35%	0.19 kg/m²
150 Mesh *	0.0024 ins	0.060 mm	46	0.0043 ins	0.109 mm	42%	0.27 kg/m²

Heanjia Super-Metals

Inconel 600 mesh high strength screening solutions

www.nickel-wiremesh.com